

PRODUCT INFORMATION**Style:** Kevlar Standard Sleeve

Sizing:	<u>Size</u>	<u>Part #</u>	
		<u>Standard</u>	<u>Thumb Hole</u>
	10"	SK-10	SK-10H
	14"	SK-14	SK-14H
	16"	SK-16	SK-16H
	18"	SK-18	SK-18H
	22"	SK-22	SK-22H
	24"	SK-24	SK-24H

**Classification:** Cut Resistant**PRODUCT DESCRIPTION**

Description: Kevlar® Standard Sleeve
Color: Yellow
Material: 100% Kevlar (2-ply knit)
Wrist: With or Without a Thumb Hole

Sold by: Dozen Pieces
Packaging (Inner Pack): 12 Pieces
Packaging (Case Pack): 288 Pieces

CUT PROTECTION PERFORMANCE INFORMATION

Test Method: ASTM F1790-97
Test Results: 1207 grams / 2.66lbs.
ANSI Level 3

ABRASION PROTECTION PERFORMANCE INFORMATION

Test Method: ASTM D3884-05
Test Results: 388 revs (cycles)

WASHING INSTRUCTIONS

Always wash similar products of the same materials together. This will eliminate different material types from being effected by non-recommended chemicals. Rinse all gloves thoroughly in cold water to ensure the release of particles in the products. If pre-soaking use luke warm water to ensure good particle softening. Mild detergents or chemicals should be used to enhance the laundering process. All products should be laundered using a mild soap and detergent. Use a warm water wash with a temperature not to exceed 160°F (71°C). Wash time should not be longer than 15 to 20 minutes. Use a rinse cycle for the product in cold water. Repeat above as often as needed to ensure a thoroughly clean product. It is important to use a high extraction speed to thoroughly remove all excess moisture. Tumble dry glove in a temperature not higher than 150°F (67°C) for a time of 15 to 20 minutes; adjustments in dry time may increase depending on quantity and weight of the products. Temperatures should not exceed 150°F (67°C).

CAUTION

Gloves are cut resistant but are not cut or puncture-proof. Do not subject to high-speed, serrated blades or intentional slashings.